FRONT
Rack Mounting Template

1U

Note: If the rack rail has round holes, install the M5 clip nuts from the installation kit.



- If you have an adjustable rack, set the distance between the front and rear EIA flanges to 719 mm (28.3 inches) outside to outside.
- Make sure that there is sufficient room in front of the front rack rail to provide minimum bezel clearance of 70 mm (2.76 inches).

1U

1U

lenovo®

P/N 00FE379
Printed in the U.S.A.

1U

1U

1U

1U

Screws required to secure rails before installing chassis

1U

Note: An extra 1U of space is required below the chassis rail for the air duct on the bottom of the chassis.

Front of Template

BACK
Rack Mounting Template

1U

Note: If the rack rail has round holes, install the M5 clip nuts from the installation kit.



- If you have an adjustable rack, set the distance between the front and rear EIA flanges to 719 mm (28.3 inches) outside to outside.
- Make sure that there is sufficient room in front of the front rack rail to provide minimum bezel clearance of 70 mm (2.76 inches).

1U

1U

1U

1U

Screws required to secure rails before installing chassis

1U

Note: An extra 1U of space is required below the chassis rail for the air duct on the bottom of the chassis.

Back of Template

NOTE TO PRINTER: Final Size 19.45 x 5. Colors: Black